

Effects for Funargs

Jeremy G. Siek, Michael M. Vitousek, and Jonathan D. Turner

University of Colorado at Boulder

jeremy.siek@colorado.edu

Abstract

Stack allocation and first-class functions don't naturally mix together. In this paper we show that a type and effect system can be the detergent that helps these features form a nice emulsion. Our interest in this problem comes from our work on the Chapel language, but this problem is also relevant to lambda expressions in C++ and blocks in Objective C. The difficulty in mixing first-class functions and stack allocation is a tension between safety, efficiency, and simplicity. To preserve safety, one must worry about functions outliving the variables they reference: the classic upward funarg problem. There are systems which regain safety but lose programmer-predictable efficiency, and ones that provide both safety and efficiency, but give up simplicity by exposing regions to the programmer. In this paper we present a simple design that combines a type and effect system, for safety, with function-local storage, for control over efficiency.

1. Introduction

This paper describes a design for integrating first-class functions into languages with stack allocation in a way that does not compromise type safety or performance and that strives for simplicity. This design is intended for use in the Chapel programming language [Chamberlain et al. 2011], but could also provide a safer alternative to the new lambda expressions of C++ [ISO 2011] and a more efficient alternative to the blocks of Objective C [Apple Inc. 2011]. The design is meant for performance-oriented languages in which the run-time overhead for each language construct should be relatively small and predictable.

The straightforward integration of first-class functions into a language with stack allocation poses type safety problems because of the classic *upward funarg problem* [Moses 1970], illustrated in Figure 1 in the Chapel language. The `compose` function returns an anonymous function which refers to parameters `f` and `g` of the surrounding `compose` function. Both `f` and `g` are functions of type `func(int,int)`; the first `int` is the input type and the second `int` is the return type. The example then defines the function `inc` and invokes `compose` to obtain `inc2`, a function that increments its argument twice. Because Chapel allocates parameters and local variables on the call stack, the variables `f` and `g` are no longer live when `inc2` is called; the call to `compose` has completed. During the call to `inc2`, the locations previously allocated to `f` and `g` may

```
proc compose(f: func(int,int),
             g: func(int,int)): func(int,int) {
    return fun(x:int){ var y=f(x); return g(y); };
}
proc inc(x: int): int { return x + 1; }
var inc2 = compose(inc, inc);
inc2(0);
```

Figure 1. Example of an upward funarg in Chapel.

contain values of types that are different from `func(int,int)`, so we have a counterexample to type safety.

To avoid the upward funarg problem, most languages with first-class functions do not allocate parameters or local variables on the stack; they allocate them on the heap and use garbage collection to reclaim the memory. However, designing garbage collection algorithms that provide predictable performance is an on-going research challenge whereas stack allocation is reliably fast [Miller and Rozas 1994]. Advanced compilers for functional languages employ static analyses to determine which variables may be safely allocated on the stack [Steele 1978, Goldberg and Park 1990, Tofte and Talpin 1994, Serrano and Feeley 1996], which improves efficiency for many programs, but still does not deliver *programmer predictable* efficiency [Tofte et al. 2004].

For the Chapel programming language, we seek a language design in which upward funargs are caught statically, thereby achieving type safety, but that enables higher-order programming and gives the programmer control over run-time costs.

While such a design is not present in the literature, the key ingredients are. Tofte and Talpin [1994, 1997] designed a typed intermediate language, which we refer to as the Region Calculus, with an explicit *region* abstraction: values are allocated into regions and regions are allocated/deallocated in a LIFO fashion. The Region Calculus uses a type and effect system *à la* Talpin and Jouvelot [1992] to guarantee the absence of memory errors, such as the dangling references that occur within upward funargs. Later work relaxed the LIFO restriction on allocation and deallocation [Aiken et al. 1995, Crary et al. 1999, Henglein et al. 2001]. Tofte et al. [2004] suggest that a programming language (as opposed to an intermediate language) with explicit regions would provide both predictable efficiency and type safety. The work by Grossman et al. [2002] on Cyclone provides evidence that this is the case.

While the type and effect systems of Tofte et al. [2004] and Grossman et al. [2002] support many higher-order programming idioms, they still disallow many useful cases that involve curried functions, such as the above `compose` function. The lambda expressions of C++ [ISO 2011] and the blocks of Objective C [Apple Inc. 2011] offer a simple solution: enable the copying of values into extra storage associated with a function. For example, in the `compose` function, the programmer could elect to copy the values of `f` and

g into storage associated with the anonymous function, thereby keeping them alive for the lifetime of the function. One might be tempted to make this copying behavior the only semantics, but in many situations the copy is too expensive [Järvi et al. 2007]. (Suppose the copied object is an array.) In the C++ design, the programmer may choose to either make the copy, incurring run-time cost in exchange for safety, or capture the reference, incurring no extra run-time cost but exposing themselves to the potential for dangling references.

We take away the following points from this prior research:

1. The Region Calculus demonstrates that a type and effect system can support many higher-order programming idioms while disallowing upward funargs.
2. Cyclone shows that only a small amount of annotations are needed to support a type and effect system.
3. The C++ and Objective C approach of providing function-local storage enables the full spectrum of higher-order programming while keeping the programmer in control of run-time costs.

In this paper we present a language design that uses a type and effect system to detect and disallow upward funargs with dangling references and that also offers the ability to copy values into function-local storage. However, unlike the Region Calculus and Cyclone, we do not expose the region abstraction to the programmer; doing so would unnecessarily complicate the language from the programmer's viewpoint. In our system, the effect of an expression is a *set of variables* instead of a set of region names. The variables in the effect are those that may be read by the expression.

For readers unfamiliar with regions, we present a static and dynamic semantics directly for our system and a syntactic proof of type safety (Section 3). The goal of this section is to provide both an aid to implementation and a direct understanding of why our type and effect system ensures type safety, and therefore also memory safety [Pierce 2002]. As an added benefit, the direct semantics supports efficient tail calls through a simple restriction in the type system that enables early deallocation. For readers familiar with regions, we present a type-preserving translation from well-typed terms of our system into the Region Calculus (Section 5).

This paper makes the following contributions:

1. We make an explicit connection between type and effect systems and the upward funarg problem so that implementers adding first-class functions to stack-based languages, such as C++, Objective-C, and Chapel, can leverage the wealth of prior work on effects.
2. We present a design that balances simplicity (for the programmer and the implementer) with safety and performance. We formalize the design in the definition of a calculus named Featherweight Functional Chapel (F²C). An interpreter and type checker for F²C are at the URL in the supplemental material.
3. We give a direct proof of type safety for F²C, show that F²C is parametric with respect to effects by constructing an erasure-based semantics, and we relate F²C to the Region Calculus through a type-preserving translation.

Section 6 places our contributions in the context of the prior research in this area and Section 7 concludes the paper.

2. Overview of the Design

We start with an overview of our design. To communicate the design as clearly and succinctly as possible, we present a small higher-order, stack-based calculus, named F²C. The calculus has explicit type and effect annotations. We point readers interested in removing the annotations to the techniques developed for Cy-

variables	x, y	
integers	n	$\in \mathbb{Z}$
operators	op	$::= + \mid - \mid \dots$
effects	φ	$::= x, \dots, x$
types	T	$::= \text{int} \mid \text{func}(T, T, [\varphi]) \mid \langle x \rangle T$
expressions	e	$::= x \mid n \mid op(e, \dots, e) \mid f$ $\mid \text{let } x = e \text{ in } e \mid \text{fix } x : T. f \mid \langle x \rangle e$
abstractions	f	$::= \text{fun}(x : T) [\varphi] \{s\} \mid \langle x \rangle f$
statements	s	$::= \text{var } x = e; s \mid \text{return } e;$ $\mid \text{var } x = \langle e \rangle; s \mid \text{return } e(e);$

Figure 2. The syntax of F²C.

clone [Grossman et al. 2002]. We first describe the syntax for F²C, defined in Figure 2, and then present the important design decisions through a series of examples.

The syntax of F²C is separated into expressions and statements to streamline the dynamic semantics.¹ This syntax can be viewed as a variant of A-normal form and there are standard techniques for translating programs into this form [Flanagan et al. 1993].

Expressions do not contain function calls or anything else that can change the stack. The expressions do include many standard things such as variables, integer literals, and primitive operator application. We sometimes use infix notation for operator application. For example, $x + z$ should be read as $+(x, z)$. More importantly, F²C has a *function creation* expression:

$$\text{fun}(x : T) [\varphi] \{s\}$$

The x is the function's parameter, of type T . In examples, we sometimes take the liberty of using functions with more than one parameter. The effect annotation φ declares the set of variables from surrounding scopes that may be referred to in the body s of the function. The type of the above function is $\text{func}(T, T', [\varphi])$ where T' is the return type of the statement s . The effect φ in the function's type is used to make sure that the function is only called when all the variables in φ are live.

There is also a `let` expression that is completely standard but plays an important role in modeling function-local storage, to be discussed shortly. The `fix` expression is also standard, and enables writing recursive functions. We include `fix` in F²C primarily to make sure our design does not accidentally rely on the assumption that all expressions terminate. We postpone discussing the remaining two forms of expressions.

The statements of F²C are also defined in Figure 2. We syntactically enforce that every control-flow path ends with a `return` statement to avoid obscuring the type system with the standard machinery for preventing functions from falling off the end [Grossman et al. 2002]. The *variable initialization* statement

$$\text{var } x = e; s$$

allocates a new location on the stack with the result of e , binding the address to the variable x , then executes statement s with x in scope. The `return` statement is standard.

Statements include two forms of function call. The *function call*

$$\text{var } x = e_1(e_2); s$$

invokes the function resulting from e_1 with the argument resulting from e_2 . The return value is placed on the stack and its address is bound to x , which can then be used in the subsequently executed statement s . The effect in the function type of e_1 must only contain

¹For the monadically inclined reader, the split almost puts F²C into monadic style with the statements in a monad for the call stack. For more on monadic regions, we refer the reader to Fluet and Morrisett [2006].

```

1 var x = 1;
2 var addx = fun(z: int)[x]{ return x + z; };
3 var twice = fun(f: func(int,int,[x]), y: int)[x] {
4     var t = f(y); return f(t);
5 };
6 var b = twice(addx, 3);
7 return b;

```

Figure 3. Example with first-class functions and stack allocation.

variables that are live in the current scope. The *tail call*

`return  $e_1(e_2)$ ;`

is a function call in which nothing else is left to be done in the current function after the call $e_1(e_2)$ returns.

Allow Downward Funargs Several variations on the example in Figure 3 serve to demonstrate the interplay between first-class functions, stack allocation, and effect annotations. The example defines a *twice* function, with a function parameter *f* that it calls *twice*, first on the parameter *y* and then on the result of the first call. The example also defines the *addx* function, which adds its parameter *z* and the global variable *x*. The example then invokes the *twice* function with *addx* as a parameter; so the *addx* argument is an example of a downward funarg.

Downward funargs are benign with respect to memory safety and are allowed by our type system. In this case, the *addx* function reads from *x*, so *x* is recorded in the type of *addx*. The call to *twice* with *addx* is allowed by the type system because the type of *addx*, including its effect, matches the type of parameter *f*. The call to *f* inside *twice* is allowed because *twice* has also declared *x* as its effect. Then looking back to the call to *twice*, it is allowed because the lifetime of variable *x* encompasses the call to *twice*.

However, the above *twice* function is surprisingly specific. It may only be called with a function that reads from *x*. We discuss shortly how to make *twice* more general.

Disallow Upward Funargs Next consider the *twice* function written in curried form, that is, taking one argument at a time as shown below. The function created on line 4 is an example of an upward funarg that is disallowed by our type system. It reads from three variables, one that is local to the function (*y*) and two from surrounding scopes (directly from *f* and indirectly from *x*). The return of this function is disallowed because the variable *f* is going out of scope, so this upward funarg contains a dangling reference.

```

3 var twice = fun(f: func(int,int,[x])) {
4     return fun(y:int)[f,x] {
5         var t = f(y); return f(t);
6     };
7 };

```

Function-local Storage In F^2C , the programmer can solve the upward funarg problem by copying *f* into function-local storage. This can be accomplished with a *let* expression, which copies (via substitution) the result of its right-hand-side into its body. With this change, the function no longer reads from *f* when it is called (the read occurs in the *let*, during the execution of *twice*), so the type system allows the return of this upward funarg from *twice*.

```

3 var twice = fun(f: func(int,int,[x])) {
4     return (let g=f
5         in fun(y:int)[x] {
6             var t = g(y); return g(t);
7         });
8 };

```

To see how this works, consider the following step of execution, where $addx \equiv \text{fun}(z:\text{int})[x]\{\text{return } x + z;\}$.

```

let g=addx in fun(y:int)[x]{var t=g(y); return g(t);}
→ fun(y:int)[x]{var t=addx(y); return addx(t);}

```

The *let* expression has caused the *addx* function to be copied into the body of the function.

Of course, a production quality compiler would not use substitution (which implies run-time code generation) but instead would use a closure representation of functions. A closure consists of a function pointer paired with an array of the values from the *let*-bound and *fix*-bound variables that occur free in the function body. For readers familiar with C++, a closure is just a “function object” or “functor” in which data members are used to store copies of the variables.

To reduce the notational overhead of adding *let* expressions, one can add syntactic sugar to function expressions for declaring that a variable be copied, as in C++ [ISO 2011]. The following shows *f* listed after the normal parameters of the function on line 4 to indicate that *f* is to be copied into function-local storage.

```

3 var twice = fun(f: func(int,int,[x])) {
4     return fun(y:int; f)[x] {
5         var t = f(y); return f(t);
6     };
7 };

```

Effect Polymorphism As described so far, the type and effect system is too restrictive because function types are annotated with specific variables. For example, the below *twice* function has a function parameter *f* that is annotated with the effect $[x]$. Thus, calling *twice* with *addx* is fine but calling *twice* with *addy* is not because the effect of *addy* is to read *y*, not *x*.

```

var x = 1;
var y = 2;
var twice = fun(f: func(int,int,[x]), y: int)[x]{
    var t = f(y); return f(t);
};
var addx = fun(z:int)[x]{ return x + z; };
var addy = fun(z:int)[y]{ return y + z; };
var b = twice(addx, 3); /* OK */
var c = twice(addy, 3); /* Error */
return b + c;

```

The solution to this problem is to parameterize functions with respect to their effects [Tofte and Talpin 1994, Pierce 2004]. In F^2C , the support for this comes from the *effect abstraction* $\langle x \rangle f$, which parameterizes its body *f* with respect to the variable *x*, and *effect application* $e \langle y \rangle$, in which the result of *e*, an effect abstraction, is instantiated by substituting *y* for *x*. As an abbreviation, we write $\langle \vec{z} \rangle f$ for $\langle z_1 \rangle \dots \langle z_n \rangle f$ and $e \langle \vec{x} \rangle$ for $e \langle x_1 \rangle \dots \langle x_n \rangle$.

To see this solution in action, we return to the previous example. This time we parameterize *twice* with respect to *p*, a place holder for a variable. The later uses of *twice* instantiate *p* with *x* and *y* respectively to get two different versions of *twice* that work with *addx* and *addy*.

```

...
var twice =
    <p> fun(f: func(int,int,[p]), y: int)[p] {
        var t = f(y); return f(t);
    };
...
var b = twice<x>(addx, 3);
var c = twice<y>(addy, 3);
return b + c;

```

Of course, we would like to parameterize with respect to arbitrary numbers of variables, so that `twice` could be used with functions with no effect or an effect with greater than one variable. See Grossman et al. [2002] for the generalization of effect polymorphism that addresses this need. From a syntactic standpoint, explicit effect application, as in `twice<x>`, is rather heavyweight. Grossman et al. [2002] also describe how to infer effect application, so we do not discuss this further here.

A programming language based on our design would provide syntactic sugar for the definition of named, effect-polymorphic, recursive functions. In this paper, we use the shorthand

```
proc <z> f(x:T1; y):T2 [φ] { s1 }
```

to mean

```
var f = (let y = y in fix f: <z> func(T1, T2, [φ]).
    <z> fun(x:T1) [φ] { s1 });
```

(The portions of the syntax related to $\bar{z}$, x , y , and φ are optional.)

Tail Calls and Effects To support space-efficient tail calls, F²C pops the current procedure call frame *prior* to performing the tail call. To make this safe, our type system does not allow tail calls to functions that read from variables on the current frame. We depart from the running example to show a classic example [Appel 1992], listed below, that was problematic for region inference. Ideally, this example uses $O(n)$ space; the approach of Tofte and Talpin [1994] used $O(n^2)$ but the later approach of Aiken et al. [1995] reduced the space to $O(n)$. Indeed, the below example uses $O(n)$ in F²C because the two calls in tail position are executed as tail calls.²

```
proc s(i:int): int list {
  if (iszero(i)) {
    return nil;
  } else {
    var p = dec(i); var sp = s(p);
    return cons(0, sp);
  }
}
proc f(n:int, x: int list):int [s]{
  var z = length(x);
  proc g(; f, n):int [s] {
    var s100 = s(100); return f(dec(n), s100);
  }
  if (iszero(n)) return 0;
  else return g();
}
var r = f(100, nil);
return r;
```

In F²C, the programmer knows for sure that every tail call does not use extra stack space. Also, the programmer is notified with an error message if a tail call could lead to a dangling reference.

Take Care with Variables Particular care must be taken with the implementation of variables in a language with a type and effect system such as F²C. The straightforward approach leads to incorrect conclusions during type checking. Consider the following program with two variables with the name x .

```
var x = 1;
proc f(a: int):int [x]{ return a + x; }
proc g(x: int):int [x]{ return f(x); }
```

²For the purposes on this example, F²C is extended with support for `if` statements and lists in the obvious way.

```
var y = g(2);
return y;
```

Inside g , the tail call `return f(x)` has the effect $\{x\}$. A naive type checking algorithm would reject this tail call because the parameter x is popped prior to the call. Of course, that is the wrong x .

A straightforward solution is for the compiler to rename all the variables in the program to ensure each name is used in a variable declaration only once. The result of such a renaming is shown below for our example.

```
var x1 = 1;
proc f1(a1: int):int [x1]{ return a1 + x1; }
proc g1(x2: int):int [x1]{ return f1(x2); }
var y1 = g1(2);
return y1;
```

Now the tail call `return f1(x2)` has the effect x_1 , which is benign because x_2 , and not x_1 , is popped prior to the call. (Another solution is to use the de Bruijn [1972] representation for variables.)

Summary of the Design The F²C calculus combines first-class functions with stack allocation, enabling the full range of higher-order programming while ensuring type safety and minimizing programmer-visible complexity through a regionless type and effect system. Further, the design gives the programmer control over efficiency by providing by-reference and by-copy options for capturing the free variables of a function.

3. Direct Semantics and Type Safety

This section presents the dynamic and static semantics of F²C and then a proof of type safety.

3.1 Dynamic Semantics

We give a substitution-based, single-step semantics for F²C that takes inspiration from the semantics of Helsen and Thiemann [2000] and Cray et al. [1999]. However, to make stack allocation explicit, the semantics operates on states of the form

$$\langle s, \kappa, \sigma, n \rangle$$

where s is the body of the currently executing function, κ is the control stack, σ is the value stack, and n is the number of stack values that are associated with the currently executing function. On a real machine, the control and value stacks are intertwined; our formalization is more clear with them separated. We write ϵ for the empty stack and $v \cdot \sigma$ for pushing v onto the front of the stack σ . (So we represent stacks as cons-style lists.) We write $|\sigma|$ for the length of stack σ and concatenation of stacks is juxtaposition, so the concatenation of σ_1 and σ_2 is written $\sigma_1 \sigma_2$.

In our semantics, variables are mapped to stack locations (represented with natural numbers). We index starting from the back of the stack so that existing locations are not disturbed by growing the stack at the front. Given the notation σ_i for the normal front-to-back indexing, we use the following notation for indexing back-to-front.

$$\sigma\{i\} = \sigma_{|\sigma|-1-i}$$

As usual in a substitution-based semantics, the syntax of the language must be slightly expanded for use by the dynamic semantics, which we show in Figure 4 with the differences highlighted in gray. The most important difference is that expressions and effects include stack locations. Stack locations have the form ℓ_T , combining the address ℓ with type T . This type annotation is ignored by the dynamic semantics (see Section 4); it is merely a technical device used in the proof of type safety. The need for these type annotations propagates to needing type annotations in variable initialization and for function return types. These type annotations are

stack index	ℓ	$\in \mathbb{N}$
stack location	l	$::= x \mid \ell_T$
effects	φ	$::= l, \dots, l$
types	T	$::= \top \mid \text{int} \mid \text{func}(T, T, [\varphi]) \mid \langle x \rangle T$
expressions	e	$::= l \mid e < \ell_T \rangle \mid \dots$
abstractions	f	$::= \text{fun}(x:T) : T[\varphi]\{s\} \mid \dots$
statements	s	$::= \text{var } x:T = e; s \mid \dots$
values	v	$::= n \mid \text{fun}(x:T) : T[\varphi]\{s\} \mid \langle x \rangle e$
value stack	σ	$::= \epsilon \mid v \cdot \sigma$
frame	F	$::= (x:T, s, n)$
stack	κ	$::= \epsilon \mid F \cdot \kappa$
state	ς	$::= \langle s, \kappa, \sigma, n \rangle$
observations	o	$::= n \mid \text{fun} \mid \text{abs}$

Figure 4. Internal syntax and run-time structures.

$\llbracket e \rrbracket_\sigma$

$$\begin{aligned}
\llbracket \ell_T \rrbracket_\sigma &= \sigma\{\ell\} \\
\llbracket n \rrbracket_\sigma &= n \\
\llbracket op(e_1, \dots, e_n) \rrbracket_\sigma &= \delta(op, (\llbracket e_1 \rrbracket_\sigma, \dots, \llbracket e_n \rrbracket_\sigma)) \\
\llbracket \text{fun}(x:T_1) : T_2[\varphi]\{s\} \rrbracket_\sigma &= \text{fun}(x:T_1) : T_2[\varphi]\{s\} \\
\llbracket \text{let } x=e_1 \text{ in } e_2 \rrbracket_\sigma &= \llbracket [x:=\llbracket e_1 \rrbracket_\sigma]e_2 \rrbracket_\sigma \\
\llbracket \text{fix } x:T. f \rrbracket_\sigma &= \llbracket [x:=\text{fix } x:T. f]f \rrbracket_\sigma \\
\llbracket \langle x \rangle f \rrbracket_\sigma &= \langle x \rangle f \\
\llbracket e < \ell_T \rangle \rrbracket_\sigma &= \llbracket [x:=\ell_T]e' \rrbracket_\sigma \quad \text{if } \llbracket e \rrbracket_\sigma = \langle x \rangle e'
\end{aligned}$$

Figure 5. Evaluation of closed expressions.

straightforward to insert during the semantic analysis (type checking) pass of a compiler. One other difference is that we add a top type $\top$ that is used by the type system to classify effect parameters. In Figure 4 we omit most of the statements because they remain unchanged with respect to Figure 2. The only change is adding a type annotation on the variable initialization form.

Figure 5 gives the evaluation of closed expressions (expressions with no free variables) to values. Evaluation is parameterized on the value stack σ so that stack locations ℓ_T can be evaluated to their associated value. Most of the equations in this definition are standard, such as the δ function that gives meaning to all the primitive operators [Plotkin 1975]. The evaluation of an effect application $e < \ell_T \rangle$ first evaluates e to an effect abstraction $\langle x \rangle e'$, substitutes ℓ_T for x in e' , and evaluates the result.

The single-step reduction relation over states is defined in Figure 6. A variable initialization statement $\text{var } x:T = e; s$ evaluates e and pushes it on the value stack then substitutes its stack location for x in s . A function call $\text{var } x=e_1(e_2); s_1$ evaluates e_1 to a function value $\text{fun}(y:T_1) : T_2[\varphi]\{x\}$, evaluates e_2 and pushes it on the value stack, substitutes its stack location for y in s , then pushes the current call frame onto the control stack. A tail call $\text{return } e_1(e_2);$ is similar except that it pops n values from the stack. (The *drop* function returns a list that lacks the first n elements of the input list.) The statement $\text{return } e;$ evaluates e , pops n values from the stack, pushes the value of e on the stack, and reinstates the top frame from the control stack, substituting the stack location of e for x in s .

Definition 1. The dynamic semantics of F^2C is specified by the partial function eval defined by the following.

$$\text{eval}(s) = \text{observe}(\llbracket e \rrbracket_\sigma) \text{ iff } \langle s, \epsilon, \epsilon, 0 \rangle \longrightarrow^* \langle \text{return } e; , \epsilon, \sigma, n \rangle$$

where observe is defined on values as follows:

$$\begin{aligned}
\text{observe}(n) &= n \\
\text{observe}(\text{fun}(x:T_1) : T_2[\varphi]\{s\}) &= \text{fun} \\
\text{observe}(\langle x \rangle e) &= \text{abs}
\end{aligned}$$

3.2 Static Semantics

As discussed in Section 2, we require that all variables be uniquely named in a pre-processing pass of a compiler.

The type system for F^2C is inductively defined in Figure 7. The judgment for well-typed expressions has the form $\Gamma; \varphi_1 \vdash e : T$ while the judgment for well-typed statements has the form $\Gamma; \varphi_1; \varphi_2 \vdash s : T$. The Γ is a type environment (symbol table), mapping variables to types, and is described in more detail below. The effect φ_1 specifies which variables may be read from; the second effect φ_2 in the context for statements keeps track of which variables are popped from the value stack upon a return from the current call frame, that is, it keeps track of the parameters and local variables. We discuss the important aspects of the type system in the following paragraphs after introducing our slightly non-standard type environments.

Type Environments We write $\emptyset$ for the empty type environment and $\Gamma, x:T$ for extending the type environment Γ with the binding of a stack-allocated variable x to type T . We write $\Gamma, x:\text{copy } T$ for extending the type environment with variables that are bound by the `let` or `fix` expressions. The copy annotation helps the type system distinguish between reads from stack-allocated variables, which count as an effect, and reads from `let`-bound or `fix`-bound variables, which do not. Looking up a variable y in an environment Γ , written $\Gamma(y)$, is defined as follows.

$$\begin{aligned}
(\Gamma, x:T)(y) &= \begin{cases} T & \text{if } x = y \\ \Gamma(y) & \text{otherwise} \end{cases} \\
(\Gamma, x:\text{copy } T)(y) &= \begin{cases} \text{copy } T & \text{if } x = y \\ \Gamma(y) & \text{otherwise} \end{cases}
\end{aligned}$$

Well-typed Expressions An occurrence of a stack-allocated variable must both be in scope and in the declared effect of the surrounding function. In contrast, a `let`-bound or `fix`-bound variable need only be in scope. During execution, stack locations are substituted for stack-allocated variables. A stack location is well typed if it is in the declared effect. This rule is simple but subtle. A well-typed program in mid execution may have functions that contain dangling stack locations. The type system ensures that such functions are never called. Thus, the typing rule for stack locations does not look at the actual value stack, but instead merely checks that the stack location is in the declared effect of the surrounding function.

A function expression is well-typed if its body is well typed in the declared effect φ_2 enlarged with parameter x . The second effect context is $\{x\}$ because x is popped from the stack upon return from this function. The typing rules for the rest of the expressions are standard.

Well-typed Statements The typing rule for variable initialization is straightforward, given that it allocates the variable on the stack. The role of the effect annotations in function types can be seen in the typing rules for function call and tail call. In both cases, the effect of the function φ_3 must be contained in the current effect φ_1 . In addition, for tail calls, φ_3 must not overlap with φ_2 , the local variables of the current function.

$\zeta \longrightarrow \zeta$

$\langle (\text{var } x:T=e; s), \kappa, \sigma, n \rangle \longrightarrow \langle [x:= \sigma _T]s, \kappa, [e]_\sigma \cdot \sigma, n+1 \rangle$	(INIT)
$\langle (\text{var } x=e_1(e_2); s_1), \kappa, \sigma, n \rangle \longrightarrow \langle [y:= \sigma _{T_1}]s_2, (x:T_2, s_1, n) \cdot \kappa, [e_2]_\sigma \cdot \sigma, 1 \rangle$	if $[e_1]_\sigma = \text{fun}(y:T_1):T_2[\varphi]\{s_2\}$ (CALL)
$\langle \text{return } e_1(e_2); \kappa, \sigma, n \rangle \longrightarrow \langle [y:=(\sigma -n)_{T_1}]s, \kappa, [e_2]_\sigma \cdot \text{drop}(n, \sigma), 1 \rangle$	if $[e_1]_\sigma = \text{fun}(y:T_1):T_2[\varphi]\{s\}$ (TAILCALL)
$\langle \text{return } e; (x:T, s, n_2) \cdot \kappa, \sigma, n_1 \rangle \longrightarrow \langle [x:=(\sigma -n_1)_T]s, \kappa, [e]_\sigma \cdot \text{drop}(n_1, \sigma), n_2+1 \rangle$	(RETURN)

Figure 6. The single-step reduction relation.

The rules for tail call and return must both prevent the escape of upward funargs with dangling references. The rules accomplish this by requiring that the free variables in the returned value's type not include any local variables. The free variables of a type, written $\text{fv}(T)$, is defined as follows.

$$\begin{aligned} \text{fv}(\text{int}) &= \emptyset \\ \text{fv}(\text{func}(T_1, T_2, [\varphi])) &= \text{fv}(T_1) \cup \varphi \cup \text{fv}(T_2) \\ \text{fv}(\langle x \rangle T) &= \text{fv}(T) - \{x\} \end{aligned}$$

3.3 Substitution vs. Environments

We originally formulated the dynamic semantics of F²C using environments instead of substitution. The authors prefer environments because they bring the semantics a step closer to a real implementation and because they more closely correspond to a programmer's view of variables. However, the definition of well-typed states became much more complex because it was difficult to define a notion of well-typed environment that interacted properly with effect polymorphism. Switching to a substitution-based semantics removed the need for well-typed environments, which simplified the definition of well-typed states and the proof of type safety.

3.4 Type Safety

Type safety for F²C means that a well-typed program cannot get stuck and that the result of the program matches its static type. The notion of *stuck* models untrapped errors such as memory errors [Cardelli 1997]. Technically, getting stuck means getting into a state that neither has a subsequent state (as defined by the step relation $\longrightarrow$) nor is a final state, as defined below.

Definition 2 (Final State). *final(ζ) if and only if the state ζ is of the form $\langle \text{return } e; \epsilon, \sigma, n \rangle$. Given a final state ζ , we write $\text{result}(\zeta)$ for $\text{observe}([e]_\sigma)$.*

The formal statement of type safety unravels the negative “not stuck” to arrive at the following positive form. The definition of a well-typed observation (for $\vdash \text{result}(\zeta) : T$ below) is given in Figure 8.

Theorem 1 (Type Safety). *If $\emptyset; \emptyset \vdash s : T$ and $\langle s, \epsilon, \epsilon, 0 \rangle \longrightarrow^* \zeta$, then either $\text{final}(\zeta)$ and $\vdash \text{result}(\zeta) : T$ or $\zeta \longrightarrow \zeta'$ for some ζ' .*

In the following, we give a proof for the Type Safety Theorem, including the statement but not the proofs of the major lemmas. (This proof is related to the proof of type safety by Helsen and Thiemann [2000] for the region calculus in that we take the syntactic approach and have a substitution-based semantics.) The proofs of the lemmas are in the accompanying technical report. (See the supplemental material.)

As usual, the proof of type safety proceeds by induction on the reduction sequence $\langle s, \epsilon, \epsilon, 0 \rangle \longrightarrow^* \zeta$. The induction step of the proof concerns a single reduction, from some intermediate state ζ_1 to the next state ζ_2 . What needs to be proved for such intermediate

 $\Gamma \vdash \varphi$

$\Gamma \vdash \varphi$ iff $\forall x \in \varphi. \exists T. \Gamma(x) = T$

 $\Gamma \vdash T$

$\Gamma \vdash T$	$\Gamma \vdash \text{int}$	$\frac{\Gamma \vdash T_1 \quad \Gamma \vdash T_2}{\Gamma \vdash \text{func}(T_1, T_2, [\varphi])}$	$\frac{\Gamma, x:T \vdash T}{\Gamma \vdash \langle x \rangle T}$
-------------------	----------------------------	--	--

 $\Gamma; \varphi \vdash e : T$

$\frac{\Gamma(x) = T \quad x \in \varphi}{\Gamma; \varphi \vdash x : T}$	$\frac{\Gamma(x) = \text{copy } T}{\Gamma; \varphi \vdash x : T}$	$\frac{\ell_T \in \varphi}{\Gamma; \varphi \vdash \ell_T : T}$
--	---	--

$\frac{\text{typeof}(op) = (T_1, \dots, T_n, T_r)}{\Gamma; \varphi \vdash e_i : T_i \text{ for } i \in \{1, \dots, n\}}$
$\frac{\Gamma; \varphi \vdash n : \text{int}}{\Gamma; \varphi \vdash op(e_1, \dots, e_n) : T_r}$

$\frac{\Gamma \vdash \text{func}(T_1, T_2, [\varphi_2]) \quad \Gamma, x:T_1; \varphi_2 \cup \{x\}; \{x\} \vdash s : T_2}{\Gamma; \varphi_1 \vdash \text{fun}(x:T_1):T_2[\varphi_2]\{s\} : \text{func}(T_1, T_2, [\varphi_2])}$
--

$\frac{\Gamma; \varphi \vdash e_1 : T_1 \quad \Gamma, x:\text{copy } T_1; \varphi \vdash e_2 : T_2}{\Gamma; \varphi \vdash \text{let } x=e_1 \text{ in } e_2 : T_2}$	$\frac{\Gamma, x:\text{copy } T; \varphi \vdash f : T}{\Gamma; \varphi \vdash \text{fix } x:T. f : T}$
$\frac{\Gamma, x : T; \emptyset \vdash e : T}{\Gamma; \varphi \vdash \langle x \rangle e : \langle x \rangle T}$	$\frac{\Gamma; \varphi \vdash e : \langle x \rangle T}{\Gamma; \varphi \vdash e \langle l \rangle : [x:=l]T}$

 $\Gamma; \varphi; \varphi \vdash s : T$

$\frac{\Gamma; \varphi_1 \vdash e : T_1 \quad \Gamma, x:T_1; \varphi_1 \cup \{x\}; \varphi_2 \cup \{x\} \vdash s : T_2}{\Gamma; \varphi_1; \varphi_2 \vdash \text{var } x:T_1=e; s : T_2}$
$\frac{\Gamma; \varphi_1 \vdash e_1 : \text{func}(T_1, T_2, [\varphi_3]) \quad \Gamma; \varphi_1 \vdash e_2 : T_1 \quad \Gamma, x:T_2; \varphi_1 \cup \{x\}; \varphi_2 \cup \{x\} \vdash s : T_3 \quad \varphi_3 \subseteq \varphi_1}{\Gamma; \varphi_1; \varphi_2 \vdash \text{var } x=e_1(e_2); s : T_3}$
$\frac{\Gamma; \varphi_1 \vdash e_1 : \text{func}(T_1, T_2, [\varphi_3]) \quad \Gamma; \varphi_1 \vdash e_2 : T_1 \quad \varphi_3 \subseteq \varphi_1 - \varphi_2 \quad \text{fv}(T_2) \cap \varphi_2 = \emptyset}{\Gamma; \varphi_1; \varphi_2 \vdash \text{return } e_1(e_2); : T_2}$
$\frac{\Gamma; \varphi_1 \vdash e : T \quad \text{fv}(T) \cap \varphi_2 = \emptyset}{\Gamma; \varphi_1; \varphi_2 \vdash \text{return } e; : T}$

Figure 7. The typing rules for expressions and statements.

$\boxed{\vdash \Gamma}$	
	$\frac{}{\vdash \emptyset} \quad \frac{\vdash \Gamma \quad \Gamma \vdash T}{\vdash \Gamma, x:T}$
$\boxed{\vdash \sigma : \Sigma}$	
	$\frac{}{\vdash \epsilon : \epsilon} \quad \frac{\emptyset; \emptyset \vdash v : T \quad \vdash \sigma : \Sigma}{\vdash v \cdot \sigma : T \cdot \Sigma}$
$\boxed{\Sigma \vdash \varphi}$	$\Sigma \vdash \varphi \equiv \forall \ell_T \in \varphi. \Sigma \{\ell\} = T$
$\boxed{\Sigma \vdash \kappa : T \Rightarrow T}$	
	$\frac{\Sigma \vdash \varphi_1 \quad \text{drop}(n, \Sigma) \vdash \varphi_1 - \varphi_2 \quad \emptyset, x:T_1; \varphi_1 \cup \{x\}; \varphi_2 \cup \{x\} \vdash s : T_2 \quad \emptyset \vdash T_1 \quad \text{drop}(n, \Sigma) \vdash \kappa : T_2 \Rightarrow T_3}{\Sigma \vdash \epsilon : T \Rightarrow T} \quad \Sigma \vdash (x:T_1, s, n) \cdot \kappa : T_1 \Rightarrow T_3$
$\boxed{\vdash \varsigma : T}$	
	$\frac{\Sigma \vdash \varphi_1 \quad \text{drop}(n, \Sigma) \vdash \varphi_1 - \varphi_2 \quad \emptyset; \varphi_1; \varphi_2 \vdash s : T_1 \quad \vdash \sigma : \Sigma \quad \text{drop}(n, \Sigma) \vdash \kappa : T_1 \Rightarrow T_2}{\vdash \langle s, \kappa, \sigma, n \rangle : T_2}$
$\boxed{\vdash o : T}$	
	$\frac{}{\vdash n : \text{int}} \quad \frac{}{\vdash \text{fun} : \text{func}(T_1, T_2, [])} \quad \frac{}{\vdash \text{abs} : \langle x \rangle T}$

Figure 8. The typing rules for states and observations.

states is that a well-typed state must either be a final state or it can take a step to another well-typed state (progress and preservation).

Lemma 1 (Step Safety). *If $\vdash \varsigma_1 : T$, then either $\text{final}(\varsigma_1)$ or $\varsigma_1 \rightarrow \varsigma_2$ and $\vdash \varsigma_2 : T$ for some ς_2 .*

The Step Safety proof hinges on the definition of well-typed states.

Well-typed States The definition of a well-typed state is given in Figure 8. Getting this definition right, such that we can prove Step Safety, is the main challenge in the overall proof of Type Safety. The definition of well-typed states relies on several auxiliary judgments which roughly correspond to the ones used by Cray et al. [1999] and Sabry [2002]. The judgment $\vdash \sigma : \Sigma$ is for well-typed value stacks, where Σ is a list of types. The judgment $\Sigma \vdash \varphi$ says that Σ satisfies φ , which is to say, any value stack of type Σ can be used to safely execute a statement that requires effect φ . The judgment $\Sigma \vdash \kappa : T_1 \Rightarrow T_2$ is for well-typed control stacks. The control stack κ is expecting a value of type T_1 (returned from the current call frame) and ultimately produces a value of type T_2 , so long as the value stack has type Σ .

The rule for a well-typed state $\langle s, \kappa, \sigma, n \rangle$ requires that the statement s be well-typed in the context of an effect declaration φ_1 and local variables φ_2 . The value stack must be well typed ($\vdash \sigma : \Sigma$) and, critically, its type Σ must satisfy the effect φ_1 which is needed to safely execute statement s . Further, popping n items from Σ must yield a stack typing that satisfies $\varphi_1 - \varphi_2$, that is, the current live variables but not including the n local variables to be popped. The typing rule for extending the control stack with a call frame is analogous to the typing rule for states, the only difference being that a call frame is expecting a return value of type T_1 that it binds to the stack-allocated variable x .

3.4.1 Expression Evaluation Safety

All of the reduction rules (Figure 6) require evaluating an expression, which means we need a notion of type safety for expressions. This is captured in the Evaluation Safety Lemma, stated below. We

only deal with closed expression ($\Gamma = \emptyset$) because, in a well-typed program, the variables are substituted away before we come to evaluate an expression. The process of evaluation replaces stack locations with their associated values, so the resulting value is well-typed in an empty effect context. There may, however, still be effects in the type T (if the value is a function and the body of the function contains stack locations). The effects in T dictate how the resulting value can be used. To ensure that the stack locations correspond to values of the appropriate type, this lemma includes the premises $\vdash \sigma : \Sigma$ and $\Sigma \vdash \varphi$.

Lemma 2 (Evaluation Safety). *If $\emptyset \vdash \varphi$, $\emptyset; \varphi \vdash e : T$, $\vdash \sigma : \Sigma$, and $\Sigma \vdash \varphi$, then $\emptyset; \emptyset \vdash \llbracket e \rrbracket_\sigma : T$.*

Looking at the various cases for evaluation in Figure 5, there are several that require knowing that a subexpression evaluates to a particular form of value. For example, to evaluate an effect application $e \langle \ell_T \rangle$, the expression e must evaluate to an effect application, which has the form $\langle x \rangle e'$. We repeat this evaluation rule below.

$$\llbracket e \langle \ell_T \rangle \rrbracket_\sigma = \llbracket [x := \ell_T] e' \rrbracket_\sigma \quad \text{if } \llbracket e \rrbracket_\sigma = \langle x \rangle e'$$

From the typing rule for $e \langle \ell_T \rangle$, we see that e has type $\langle x \rangle T'$ for some T' , and by the induction hypothesis, the value $\llbracket e \rrbracket_\sigma$ also has type $\langle x \rangle T'$. The Canonical Forms Lemma, stated below, tells us that the value $\llbracket e \rrbracket_\sigma$ must therefore be an effect abstraction (and similar facts about the other types).

Lemma 3 (Canonical Forms). *If $\emptyset; \emptyset \vdash v : T$, then exactly one of the following holds.*

1. $T = \text{int}$ and $v = n$ for some n , or
2. $T = \text{func}(T_1, T_2, [\varphi])$ and $v = \text{fun}(x:T_1):T_2[\varphi]\{s\}$ for some x, T_1, T_2, φ, s , or
3. $T = \langle x \rangle T'$ and $v = \langle x \rangle e$ for some x and e .

The evaluation rules for **let** and **fix** involve substituting a (closed) expression for a variable. Thus, we need to know that substitution, given well-typed expressions, produces a well-typed expression. Because expressions contain statements, and vice versa, this Lemma must be proved simultaneously for expressions and statements.

Lemma 4 (Substitution Preserves Types).

Suppose that $\emptyset; \emptyset \vdash e : T_1$ and $\vdash \Gamma_1, x:T_1, \Gamma_2$.

1. *If $\Gamma_1, x:T_1, \Gamma_2; \varphi_1 \vdash e_1 : T_2$, then $\Gamma_1, \Gamma_2; \varphi_1 \vdash [x := e]e_1 : T_2$.*
2. *If $\Gamma_1, x:T_1, \Gamma_2; \varphi_1; \varphi_2 \vdash s : T_2$, then $\Gamma_1, \Gamma_2; \varphi_1; \varphi_2 \vdash [x := e]s : T_2$.*

Such a substitution lemma often takes a different form, with no Γ_2 , and instead relies on a Permutation Lemma to keep the binding for x on the right-most end of the type environment while going under a function expression. However, we can not permute environments in F^2C because variables may appear in types, so the particular sequencing of variables in the environment is rather important. (For similar reasons, permutation does not hold in polymorphic calculi such as System F.) The expression e being substituted-in may be spliced into a context with a different typing environment with possibly many variables in scope. This is irrelevant to the typing of e because e does not have any free variables. The following Environment Weakening Lemma makes this precise.

Lemma 5 (Environment Weakening).

Suppose $\vdash \Gamma, \emptyset \vdash \varphi_1$, and $\emptyset \vdash \varphi_2$.

1. *If $\emptyset; \varphi_1 \vdash e : T$, then $\Gamma; \varphi_1 \vdash e : T$.*
2. *If $\emptyset; \varphi_1; \varphi_2 \vdash s : T$, then $\Gamma; \varphi_1; \varphi_2 \vdash s : T$.*

The expression e being substituted also goes from a context with no effects to a context with possibly many effects. Thus, we

also need weakening for effects. The following Effect Weakening Lemma does not need to be proved simultaneously for statements because the typing of the body of a function does not depend on the current effect.

Lemma 6 (Effect Weakening). *If $\Gamma; \varphi \vdash e : T$, $\varphi \subseteq \varphi'$, and $\Gamma \vdash \varphi'$, then $\Gamma; \varphi' \vdash e : T$.*

The evaluation rule for effect application involves substituting a stack location for a variable. Substituting stack locations is more involved than substituting expressions because stack locations occur in effects and therefore in types. The proof that substitution of stack locations preserves types requires simultaneously proving this property for types, expressions, and statements.

Lemma 7 (Substitution of Stack Locations Preserves Types).

Let $[X]$ stand for $[x := \ell_{T_1}]X$ in the following.

Suppose $\Gamma_1, x:T_1, \Gamma_2 \vdash \varphi_1$ and $\Gamma_1, x:T_1, \Gamma_2 \vdash \varphi_2$.

1. *If $\Gamma_1, x:T_1, \Gamma_2 \vdash T_2$, then $\Gamma_1, [\Gamma_2] \vdash [T_2]$.*
2. *If $\Gamma_1, x:T_1, \Gamma_2; \varphi_1 \vdash e : T_2$, then $\Gamma_1, [\Gamma_2]; [\varphi_1] \vdash [e] : [T_2]$.*
3. *If $\Gamma_1, x:T_1, \Gamma_2; \varphi_1; \varphi_2 \vdash s : T_2$, then $\Gamma_1, [\Gamma_2]; [\varphi_1]; [\varphi_2] \vdash [s] : [T_2]$.*

Of course, to handle the case of evaluating a primitive operator, we require that all the primitive operators be type safe.

Constraint 1 (Type safe primitive operators). *If $\text{typeof}(op) = (T_1, \dots, T_n, T_r)$ and $\emptyset; \emptyset \vdash v_i : T_i$ for $i \in \{1, \dots, n\}$, then $\delta(op, (v_1, \dots, v_n)) = v'$ and $\emptyset; \emptyset \vdash v' : T_r$ for some v' .*

No other lemmas are required to prove Evaluation Safety.

3.4.2 Step Safety

The proof of Step Safety requires a few more key lemmas. Lemma 8 is a consequence of how the type system is designed to prevent upward funargs, that is, the return of functions with dangling references to local variables.

Lemma 8 (Locals not in Return Type). *Suppose $\Gamma \vdash \varphi_1$ and $\Gamma \vdash \varphi_2$. If $\Gamma; \varphi_1; \varphi_2 \vdash s : T$, then $\text{fv}(T) \cap \varphi_2 = \emptyset$.*

The substitution of stack addresses into the return type of a function doesn't change the return type (which would break type preservation), because of the above lemma together with the following.

Lemma 9 (Substitution of Non-free Variables). *If $x \notin \text{fv}(T)$, then $[x := \ell_{T'}]T = T$.*

A function may have fewer effects than are present in the calling context, so we need the following weakening lemma.

Lemma 10 (Satisfaction Weakening). *If $\Sigma \vdash \varphi_1$ and $\varphi_2 \subseteq \varphi_1$, then $\Sigma \vdash \varphi_2$.*

Finally, in tail calls and when returning from a function, we pop the values corresponding to parameters and local variables from the stack, but the remaining stack is still well typed.

Lemma 11 (Drop Stack). *If $\vdash \sigma : \Sigma$, then $\vdash \text{drop}(n, \sigma) : \text{drop}(n, \Sigma)$.*

The proof of Step Safety (Lemma 1) then proceeds by case analysis on the statement component of the state ς_1 .

4. Erasure-based Semantics

An important question from both the semantic and implementation perspective is whether the execution of an effect abstraction depends in any way on the effects with which it is instantiated. We answer this question in the negative by demonstrating that F^2C can be implemented using an erasure-based approach. A more direct argument for this property, known as relational parametricity, can be

$[x]$	$=$	x
$[n]$	$=$	n
$[op(e_1 \dots e_n)]$	$=$	$op([e_1] \dots [e_n])$
$[\text{let } x=e_1 \text{ in } e_2]$	$=$	$\text{let } x=[e_1] \text{ in } [e_2]$
$[\text{fix } x:T. f]$	$=$	$\text{fix } x. [f]$
$[e \langle \ell \rangle]$	$=$	$[e]$
$[\text{fun}(x:T) : T[\varphi] \{s\}]$	$=$	$\text{fun}(x) \{[s]\}$
$[\langle x \rangle f]$	$=$	$[f]$
$[\text{var } x:T=e; s]$	$=$	$\text{var } x=[e]; [s]$
$[\text{var } x=e_1(e_2); s]$	$=$	$\text{var } x=[e_1]([e_2]); [s]$
$[\text{return } e_1(e_2);]$	$=$	$\text{return } [e_1]([e_2]);$
$[\text{return } e;]$	$=$	$\text{return } [e];$

Figure 9. Erasure function

accomplished via a proof based on logical relations, but we leave that for future work.

Concretely, because effect abstractions do not depend on their arguments, it is unnecessary to perform effect substitutions at runtime. In the direct semantics of F^2C , evaluation of effect applications $e \langle \ell \rangle$ involves substitution of the stack location ℓ_T into the subterms of e . However, since effect abstraction variables may be substituted by concrete variables of any type, effect variables may only be used in effect applications and function effect annotations, which do not interact with the rest of the program at runtime — in other words, F^2C programs are parametric with regard to effect polymorphism.

We remove both the type and effect annotations by an erasure function, defined in Figure 9. We even erase effect abstractions and effect applications. The syntactic restriction in F^2C that the body of an effect abstraction is an abstraction (a value) means that there is no need to delay the evaluation of the body (because the body is already a value).

We may evaluate erased programs with similar rules to those which evaluate F^2C and we refer to the resulting evaluation function as $\text{eval}_{\text{erased}}$. The similarity of these rules to those for F^2C leads us to the following:

Proposition 1 (Preservation of semantics under erasure). *If $\emptyset; \emptyset \vdash s : T$, then $\text{eval}(s) = \text{eval}_{\text{erased}}([s])$.*

We have performed rigorous testing of this property and found no violations. It should be straightforward to prove this preservation of semantics via a simulation argument.

5. Translation to the Region Calculus

In this section we relate F^2C to a region calculus, in particular, a calculus similar to Henglein's ETL and RTL calculi [Pierce 2004]. The goal of this section is not to provide an aid to implementation, but to aid the reader in understanding the relation between our work and prior work on regions. Thus, we choose a relatively prototypical region calculus at the cost of losing efficient tail calls. (There are other region-based calculi that would enable efficient tail calls [Aiken et al. 1995, Cray et al. 1999].)

The syntax for the region calculus is defined in Figure 10. The type system is standard [Pierce 2004]. We use the variable r to range over expressions, to easily distinguish region calculus expressions from F^2C expressions. The form $\text{new } \rho. r$ allocates an empty region and binds it to the name ρ for use in r . The form r at ρ allocates a location in region ρ , evaluates expression r and stores its value into that location, then returns the location. The form $r! \rho$ evaluates r to a location and dereferences the location, that is, extracts the value stored at that location of region ρ . In

region variables	ρ
effects	$\varphi ::= \{\rho, \dots, \rho\}$
types	$T ::= \text{int} \mid T \xrightarrow{\varphi} T \mid \forall \rho. T \mid T \text{ at } \rho$
expressions	$r ::= x \mid n \mid \text{op}(r, \dots, r) \mid \lambda x. r \mid r r \mid \text{fix } x. r \mid \text{new } \rho. r \mid r \text{ at } \rho \mid r ! \rho \mid \Lambda \rho. r \mid r[\rho]$

Figure 10. A region calculus

addition to the forms in Figure 10, we use the following syntactic sugar: $\text{let } x=r_1 \text{ in } r_2 \triangleq (\lambda x. r_2) r_1$.

Figure 11 shows our translation from F²C to the region calculus. The translation functions take two parameters, the first some syntax (expressions, etc.) and the second a partial function from variables to regions. The main idea behind the translation is that we allocate a new region for each variable that is stack allocated in F²C. This idea is realized in the translation for initialization statements shown below. The $\text{new } \rho$ allocates the region for the variable x and the expression $\llbracket e \rrbracket_R \text{ at } \rho$ assigns the value of e into a new location in the region. This location is bound to x . The following statement s is translated using the mapping $R(x:=\rho)$, that is, extending R with the association of region ρ to x .

$$\llbracket \text{var } x=e; s \rrbracket_R = \text{new } \rho. \text{let } x=\llbracket e \rrbracket_R \text{ at } \rho \text{ in } \llbracket s \rrbracket_{R(x:=\rho)}$$

where ρ is fresh

The second half of the story is the translation of variable occurrences. If R associates a region ρ with the variable x , then we translate the variable x to $x ! \rho$, which dereferences the location that is bound to x . Otherwise, the variable x must have been bound by either a let or fix , in which case there is no need to dereference.

$$\llbracket x \rrbracket_R = \begin{cases} x ! \rho & \text{if } R(x) = \rho \\ x & \text{otherwise} \end{cases}$$

The translation from F²C to this region calculus is type preserving, that is, it maps well-typed programs to well-typed programs. The proof is in the accompanying technical report.

Theorem 2 (Translation to Regions Preserves Types). *Suppose $\Gamma \vdash R$, $\Gamma \vdash \varphi_1$, and $\Gamma \sim_R \Gamma_r$.*

1. If $\Gamma; \varphi_1 \vdash e : T$, then $\Gamma_r; \llbracket \varphi_1 \rrbracket_R \vdash \llbracket e \rrbracket_R : \llbracket T \rrbracket_R$.
2. If $\Gamma; \varphi_1; \varphi_2 \vdash s : T$, then $\Gamma_r; \llbracket \varphi_1 \rrbracket_R \vdash \llbracket s \rrbracket_R : \llbracket T \rrbracket_R$.

We already proved type safety in Section 3.4 with respect to the direct semantics of F²C. With Theorem 2 in hand, we could write an alternative proof that relies on the type safety of the region calculus.

The translation to regions is also semantics preserving. That is, evaluating a program s under the direct semantics yields the same result as translating the program and then evaluating under the dynamic semantics of the region calculus [Pierce 2004], for which we use the name $\text{eval}_{\mathcal{R}}$. We have tested this property on numerous programs and have found no violations. The proof of this should be straightforward using a simulation argument.

Proposition 2 (Semantics Preserving). *If $\emptyset; \emptyset; \emptyset \vdash s : T$, then $\text{eval}(s) = \text{eval}_{\mathcal{R}}(\llbracket s \rrbracket_{\emptyset})$.*

6. Related Work

Here we place the design of F²C in relation to other points in the design space. To the best of our knowledge, F²C provides a unique balance of safety, efficiency, and simplicity through its combination

$\llbracket T \rrbracket_R$	$\llbracket \text{int} \rrbracket_R = \text{int}$
	$\llbracket \text{func}(T_1, T_2, [\varphi]) \rrbracket_R = \llbracket T_1 \rrbracket_R \xrightarrow{[\varphi]^R} \llbracket T_2 \rrbracket_R$
	$\llbracket \langle x \rangle T \rrbracket_R = \forall \rho. \llbracket T \rrbracket_{R(x:=\rho)}$
$\llbracket e \rrbracket_R$	$\llbracket x \rrbracket_R = \begin{cases} x ! \rho & \text{if } R(x) = \rho \\ x & \text{otherwise} \end{cases}$
	$\llbracket n \rrbracket_R = n$
	$\llbracket \text{op}(e_1, \dots, e_n) \rrbracket_R = \text{op}(\llbracket e_1 \rrbracket_R, \dots, \llbracket e_n \rrbracket_R)$
	$\llbracket \text{fun}(x:T_1):T_2[\varphi]\{s\} \rrbracket_R = \lambda y. \text{new } \rho. \text{let } x=y \text{ at } \rho \text{ in } \llbracket s \rrbracket_{R(x:=\rho)}$
	where y, ρ are fresh
	$\llbracket \langle x \rangle f \rrbracket_R = \Lambda \rho. \llbracket f \rrbracket_{R(x:=\rho)}$
	where ρ is fresh
	$\llbracket \text{let } x=e_1 \text{ in } e_2 \rrbracket_R = \text{let } x=\llbracket e_1 \rrbracket_R \text{ in } \llbracket e_2 \rrbracket_R$
	$\llbracket \text{fix } x:T. f \rrbracket_R = \text{fix } x. \llbracket f \rrbracket_R$
	$\llbracket e \langle x \rangle \rrbracket_R = \llbracket e \rrbracket_R[R(x)]$
$\llbracket s \rrbracket_R$	$\llbracket \text{var } x=e; s \rrbracket_R = \text{new } \rho. \text{let } x=\llbracket e \rrbracket_R \text{ at } \rho \text{ in } \llbracket s \rrbracket_{R(x:=\rho)}$
	where ρ is fresh
	$\llbracket \text{var } x=e_1(e_2); s \rrbracket_R = \text{new } \rho. \text{let } x=e \text{ in } \llbracket s \rrbracket_{R(x:=\rho)}$
	where ρ is fresh and $e = (\llbracket e_1 \rrbracket_R \llbracket e_2 \rrbracket_R) \text{ at } \rho$
	$\llbracket \text{return } e_1(e_2); \rrbracket_R = \llbracket e_1 \rrbracket_R \llbracket e_2 \rrbracket_R$
	$\llbracket \text{return } e; \rrbracket_R = \llbracket e \rrbracket_R$
$\Gamma \sim_R \Gamma_r$	$\frac{}{\emptyset \sim_R \emptyset} \quad \frac{T \neq \top \quad \Gamma \sim_R \Gamma_r}{(\Gamma, x:T) \sim_R (\Gamma_r, y:\llbracket T \rrbracket_R, x:\llbracket T \rrbracket_R \text{ at } R(x))}$
	$\frac{T \neq \top \quad \Gamma \sim_R \Gamma_r}{(\Gamma, x:T) \sim_R (\Gamma_r, x:\llbracket T \rrbracket_R \text{ at } R(x))}$
	$\frac{\Gamma \sim_R \Gamma_r}{(\Gamma, x:T) \sim_R \Gamma_r} \quad \frac{\Gamma \sim_R \Gamma_r}{(\Gamma, x:\text{copy } T) \sim_R (\Gamma_r, x:\llbracket T \rrbracket_R)}$
$\llbracket \varphi \rrbracket_R$	$\llbracket \varphi \rrbracket_R = \{R(x) \mid x \in \varphi\}$
$\Gamma \vdash R$	$\forall x. (\exists T. \Gamma(x) = T) \text{ iff } (\exists \rho. R(x) = \rho)$

Figure 11. Translation of F²C to a region calculus.

of a regionless type and effect system and programmer controlled function-local storage.

Efficient but unsafe The lambda expressions of C++ [ISO 2011, Järvi et al. 2007] give programmers control over whether to capture references to variables or to make copies. The design of F²C offers the addition of static checking to catch upward funargs with dangling references.

Safe but less efficient The blocks in Objective C [Apple Inc. 2011] give programmers a choice between copying the value of a variable into function-local storage (the default) or storing the variable on the heap (called `_block` storage) with automatic memory management. Unfortunately, neither of these options is ideal for the most common use case for first-class functions: downward funargs.

In such situations, storing the variable on the stack and capturing a reference to it is both safe and the most efficient.

Safe but efficiency is less predictable Compilers for garbage-collected languages, such as Java, Standard ML, and Scheme, optimize memory allocation by performing static analyses (such as escape analysis [Goldberg and Park 1990, Choi et al. 1999], region inference [Tofte and Talpin 1994], and storage use analysis [Serrano and Feeley 1996]) to decide when objects can use a FIFO memory management scheme. However, from the programmer standpoint, whether the static analyses succeeds on a given program is unpredictable, which in turn means that the time and space efficiency of the program is unpredictable [Tofte et al. 2004]. The design of F²C offers an alternative in which programmers can mandate the stack allocation of objects, thereby achieving predictable efficiency.

Safe and efficient, but complex Several programming languages employ type and effect systems to provide safety and efficiency, but at the cost of exposing regions to the programmer [Grossman et al. 2002, Boyapati et al. 2003]. (Several intermediate representations also use explicit regions, but because they are intermediate representations, regions are not necessarily exposed to the programmer [Crary et al. 1999, Tofte and Talpin 1994].) Instead of regions, the F²C design relies on traditional stack allocation where parameters and local variables are implicitly allocated on the stack. The effects of F²C are sets of variables instead of sets of region names.

7. Conclusion

This paper presents a design for mixing first-class functions and stack allocation that ensures type safety, enables the full range of higher-order programming, and gives the programmer control over efficiency while minimizing programmer-visible complexity. The design uses a type and effect system based on variables instead of region names. The system allows downward funargs and disallows upward funargs with dangling references. To facilitate safe upward funargs, the design gives programmers the choice of copying values into function-local storage. The paper formalizes the design in the F²C calculus, defining its syntax, type system, and dynamic semantics, and gives a proof of type safety. This paper also demonstrates that F²C is parametric with respect to effects so effect abstractions can be implemented via erasure. Finally, the paper relates F²C to a region calculus through a type-directed translation.

References

- A. Aiken, M. Fähndrich, and R. Levien. Better static memory management: improving region-based analysis of higher-order languages. In *Proceedings of the ACM SIGPLAN 1995 conference on Programming language design and implementation*, PLDI '95, pages 174–185, New York, NY, USA, 1995. ACM. doi: <http://doi.acm.org/10.1145/207110.207137>.
- A. W. Appel. *Compiling with continuations*. Cambridge University Press, New York, NY, USA, 1992. ISBN 0-521-41695-7.
- Apple Inc. Blocks programming topics. Technical report, Apple Inc., Cupertino, CA, March 2011.
- C. Boyapati, A. Salcianu, W. Beebe, Jr., and M. Rinard. Ownership types for safe region-based memory management in real-time java. In *Proceedings of the ACM SIGPLAN 2003 conference on Programming language design and implementation*, PLDI '03, pages 324–337, New York, NY, USA, 2003. ACM. doi: <http://doi.acm.org/10.1145/781131.781168>.
- L. Cardelli. *Handbook of Computer Science and Engineering*, chapter Type Systems. CRC Press, 1997.
- B. Chamberlain, S. Deitz, S. Hoffswell, J. Plevyak, H. Zima, and R. Diaconescu. *Chapel Specification*. Cray Inc, 0.82 edition, October 2011.
- J.-D. Choi, M. Gupta, M. Serrano, V. C. Sreedhar, and S. Midkiff. Escape analysis for java. In *OOPSLA '99: Proceedings of the 14th ACM SIGPLAN conference on Object-oriented programming, systems, languages, and applications*, pages 1–19, New York, NY, USA, 1999. ACM Press.
- K. Crary, D. Walker, and G. Morrisett. Typed memory management in a calculus of capabilities. In *Proceedings of the 26th ACM SIGPLAN-SIGACT symposium on Principles of programming languages*, POPL '99, pages 262–275, New York, NY, USA, 1999. ACM. doi: <http://doi.acm.org/10.1145/292540.292564>.
- N. de Bruijn. Lambda calculus notation with nameless dummies, a tool for automatic formula manipulation, with application to the Church-Rosser theorem. *Indagationes Mathematicae (Proceedings)*, 75(5):381–392, 1972. doi: [10.1016/1385-7258\(72\)90034-0](http://doi.acm.org/10.1016/1385-7258(72)90034-0).
- C. Flanagan, A. Sabry, B. F. Duba, and M. Felleisen. The essence of compiling with continuations. In *PLDI '93: Proceedings of the ACM SIGPLAN 1993 conference on Programming language design and implementation*, pages 237–247, New York, NY, USA, 1993. ACM Press.
- M. Fluet and G. Morrisett. Monadic regions. *J. Funct. Program.*, 16(4-5): 485–545, 2006.
- B. Goldberg and Y. G. Park. Higher order escape analysis. In *ESOP*, 1990.
- D. Grossman, G. Morrisett, T. Jim, M. Hicks, Y. Wang, and J. Cheney. Region-based memory management in cyclone. In *PLDI '02: Proceedings of the ACM SIGPLAN 2002 Conference on Programming language design and implementation*, pages 282–293, New York, NY, USA, 2002. ACM Press.
- S. Helsen and P. Thiemann. Syntactic type soundness for the region calculus. In *4th International Workshop on Higher Order Operational Techniques in Semantics (HOOTS 2000)*, volume 41 of ENTCS, pages 1–19. Elsevier, 2000.
- F. Henglein, H. Makhholm, and H. Niss. A direct approach to control-flow sensitive region-based memory management. In *Proceedings of the 3rd ACM SIGPLAN international conference on Principles and practice of declarative programming*, PPDP '01, pages 175–186, New York, NY, USA, 2001. ACM. doi: <http://doi.acm.org/10.1145/773184.773203>.
- ISO. Working draft, standard for programming language C++. Technical Report N3242, ISO, February 2011.
- J. Järvi, J. Freeman, and L. Crowl. Lambda expressions and closures for c++ (revision 1). Technical Report N2329, ISO/IEC JTC 1 SC22 WG21, June 2007.
- J. S. Miller and G. J. Rozas. Garbage collection is fast, but a stack is faster. AI Memos AIM-1462, MIT Artificial Intelligence Lab, March 1994.
- J. Moses. The function of FUNCTION in LISP or why the FUNARG problem should be called the environment problem. *SIGSAM Bull.*, pages 13–27, July 1970. doi: <http://doi.acm.org/10.1145/1093410.1093411>.
- B. C. Pierce. *Types and Programming Languages*. MIT Press, 2002.
- B. C. Pierce, editor. *Advanced Topics in Types and Programming Languages*. The MIT press, 2004.
- G. D. Plotkin. Call-by-name, call-by-value and the lambda-calculus. *Theoretical Computer Science*, 1(2):125–159, December 1975.
- A. Sabry. MinML: Syntax, static semantics, dynamic semantics, and type safety. Course notes for b522, February 2002.
- M. Serrano and M. Feeley. Storage use analysis and its applications. In *Proceedings of the first ACM SIGPLAN international conference on Functional programming*, ICFP '96, pages 50–61, New York, NY, USA, 1996. ACM. doi: <http://doi.acm.org/10.1145/232627.232635>.
- G. L. Steele. Rabbit: A compiler for Scheme. Technical report, Cambridge, MA, USA, 1978.
- J.-P. Talpin and P. Jouvelot. The type and effect discipline. In *Logic in Computer Science*, 1992. *LICS '92., Proceedings of the Seventh Annual IEEE Symposium on*, pages 162–173, jun 1992. doi: [10.1109/LICS.1992.185530](http://doi.acm.org/10.1109/LICS.1992.185530).
- M. Tofte and J.-P. Talpin. Implementation of the typed call-by-value lambda-calculus using a stack of regions. In *POPL '94: Proceedings of the 21st ACM SIGPLAN-SIGACT symposium on Principles of programming languages*, pages 188–201. ACM Press, 1994.

- M. Tofte and J.-P. Talpin. Region-based memory management. *Inf. Comput.*, 132(2):109–176, 1997.
- M. Tofte, L. Birkedal, M. Elsmann, and N. Hallenberg. A retrospective on region-based memory management. *Higher-Order and Symbolic Computation Journal*, 17:245–265, 2004.